



























MODEL	PICTURE	TYPE	DECCRIPTION	PACKAGIN G
MD-6021F-36	  <p style="color: red; text-align: center;"><b>REMOTE FLASH LIGHT</b></p> 	7.5" 36W	<ul style="list-style-type: none"> <li>. 3W Cree each LED</li> <li>. Operating Volt: 10-30Volt DC</li> <li>. Color temperature: 6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate: IP67</li> <li>. Beam: Spot beam,flood beam,combo beam</li> <li>. Material: Diecast aluminum housing</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. LENS: PC</li> <li>. About 30000 hours life time</li> <li>. Housing color: Black</li> <li>50m Wireless remote distance</li> <li>6flash beam pattern optional</li> <li>A:switch on white color; B:switch on amber color; C:Press 1st:fast flashing of white color; Press 2nd:slow flashing of white color; Press 3rd:SOS of white color; Press 4th: fast flashing of amber color; Press 5th:slow flashing of amber color; D:Swiith off</li> </ul>	6 PC/CTN
MD-6021F-72		13" 72W		6 PC/CTN
MD-6021F-120		22" 120W		6 PC/CTN
MD-6021F-180		33" 180W		4 PC/CTN
MD-6021F-240		42" 240W		4 PC/CTN
MD-6021F-288		50" 288W		4 PC/CTN
MD-6018D-56	  	10.5" 56W	<ul style="list-style-type: none"> <li>. 3W each CREE LED at both sides, 10W Cree LED in middle</li> <li>. Operating Volt: 10-30Volt DC</li> <li>. Color temperature:6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate:IP67</li> <li>. Beam:spot beam,flood beam,combo beam</li> <li>. Material:diecast aluminum housing</li> <li>. Mounting Bracket:304 stainless steel bracket,both side bracket and bottom bracket available</li> <li>. LENS:PC LENS</li> <li>. About 50000 hours life time</li> <li>. Housing color: Black</li> <li>. Three wires cable provides 3 functions. Can light in spot beam, flood beam and combo beam</li> </ul>	12 PC/CTN
MD-6018D-76		13.5" 76W		12 PC/CTN
MD-6018D-96		17" 96W		6 PC/CTN
MD-6018D-116		20" 116W		6 PC/CTN
MD-6018D-132		23" 132W		6 PC/CTN
MD-6018D-152		26" 152W		6 PC/CTN
MD-6018D-192		32" 192W		6 PC/CTN
MD-6018D-248		41" 248W		4 PC/CTN
MD-6018D-284		47" 284W		4 PC/CTN
MD-6018D-304		50" 304W		4 PC/CTN

MD-6021E-36	    	7.5" 36W	<ul style="list-style-type: none"> <li>. 3W Epistar each LED</li> <li>. Operating Volt: 10-30Volt DC</li> <li>. Color temperature: 6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate: IP67</li> <li>. Beam: Spot beam,flood beam,combo beam</li> <li>. Material: Diecast aluminum housing</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. LENS: PC</li> <li>. About 30000 hours life time</li> <li>. Housing color: Black</li> </ul>	6 PC/CTN
MD-6021E-72		13" 72W		6 PC/CTN
MD-6021E-120		22" 120W		6 PC/CTN
MD-6021E-180		33" 180W		4 PC/CTN
MD-6021E-240		42" 240W		4 PC/CTN
MD-6021E-288		50" 288W		4 PC/CTN
MD-6021C-36	    	7.5" 36W	<ul style="list-style-type: none"> <li>. 3W Cree each LED</li> <li>. Operating Volt: 10-30Volt DC</li> <li>. Color temperature: 6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate: IP67</li> <li>. Beam: Spot beam,flood beam,combo beam</li> <li>. Material: Diecast aluminum housing</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. LENS: PC</li> <li>. About 50000 hours life time</li> <li>. Housing color: Black</li> </ul>	6 PC/CTN
MD-6021C-72		13" 72W		6 PC/CTN
MD-6021C-120		22" 120W		6 PC/CTN
MD-6021C-180		33" 180W		4 PC/CTN
MD-6021C-240		42" 240W		4 PC/CTN
MD-6021C-288		50" 288W		4 PC/CTN
MD-6024-18	   	4" 18W	<ul style="list-style-type: none"> <li>. 3W Cree each LED</li> <li>. Operating Volt: 10-30Volt DC</li> <li>. Color temperature: 6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate: IP67</li> <li>. Beam: Spot beam,flood beam,combo beam</li> <li>. Material: Diecast aluminum housing</li> <li>. Mounting Bracket: stainless steel bottom bracket</li> <li>. LENS: PC</li> <li>. About 50000 hours life time</li> <li>. Housing color: Black</li> </ul>	18 PC/CTN
MD-6024-36		6.6" 36W		12 PC/CTN
MD-6024-54		9.3" 54W		12 PC/CTN
MD-6024-72		12" 72W		6 PC/CTN
MD-6024-90		14.6" 90W		6 PC/CTN
MD-6024-108		17.2" 108W		6 PC/CTN
MD-6024-126		20" 126W		6 PC/CTN
MD-6024-180		28" 180W		6 PC/CTN
MD-6024-234		36" 234W		4 PC/CTN
MD-6024-288		45" 288W		

MD-6027-40		4.5" 40 W	. 10W each CREE LED . Color temperature:5000K, 6500K . Operation temperature -40°C~60°C . Waterproof rate:IP67	12PC/CTN
MD-6027-80		8"80 W	. Beam:spot beam, flood beam,combo	6PC/CTN
MD-6027-120		10.5" 120 W	. Material:diecast aluminum housing . Mounting Bracket:stainless steel bracket.	6PC/CTN
MD-6027-200		17"200 W	. LENS:PC	4PC/CTN
MD-6027-240		20"240 W	. Housing color:Black, . other housing colors available . EMC compatible	4PC/CTN
MD-6028-18		4.5" 18W	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C~60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket:304 stainless steel bracket,both side bracket and bottom bracket available . LENS: PC . About 50000 hours life time . Housing color: Black	18 PC/CTN
MD-6028-36		8" 36W		12 PC/CTN
MD-6028-54		10.5" 54W		12 PC/CTN
MD-6028-72		13.5" 72W		6 PC/CTN
MD-6028-90		14.5" 90W		6 PC/CTN
MD-6028-108		20" 108W		6 PC/CTN
MD-6028-126		23" 126W		6 PC/CTN
MD-6028-144		26" 144W		6 PC/CTN
MD-6028-180		32" 180W		6 PC/CTN
MD-6028-234		42" 234W		4 PC/CTN
MD-6028-270		48" 270W		4 PC/CTN
MD-6028-288		50" 288W		4 PC/CTN
MD-6029E-72				13" 72W
MD-6029E-120	22" 120W		6 PC/CTN	
MD-6029E-180	33" 180W		4 PC/CTN	
MD-6029E-240	42" 240W		4 PC/CTN	
MD-6029E-288	50" 288W		4 PC/CTN	
MD-6029E-300	52" 300W		4 PC/CTN	
MD-6029E-312	54" 312W		4 PC/CTN	

MD-6029C-72		13" 72W	<ul style="list-style-type: none"> <li>. 3W Cree each LED</li> <li>. Operating Volt: 10-30Volt DC</li> <li>. Color temperature: 6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate: IP67</li> <li>. Beam: Spot beam,flood beam,combo beam</li> <li>. Material: Diecast aluminum housing</li> <li>. Mounting Bracket: Stainless steel bracket</li> <li>. LENS: PC</li> <li>. About 30000 hours life time</li> <li>. Housing color: Black</li> </ul>	6 PC/CTN
MD-6029C-120		22" 120W		6 PC/CTN
MD-6029C-180		33" 180W		4 PC/CTN
MD-6029C-240		42" 240W		4 PC/CTN
MD-6029C-288		50" 288W		4 PC/CTN
MD-6029C-300		52" 300W		4 PC/CTN
MD-6029C-312		54" 312W		4 PC/CTN
MD-6017D-60		6" 60 Watt	<ul style="list-style-type: none"> <li>. CREE XML LED 10W/PC</li> <li>. Operating Volt: 10-80Volt DC</li> <li>. Color temperature: 6000K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate: IP67</li> <li>. Beam:spot beam, flood beam and combo beam</li> <li>. Color: white, amber, white+amber</li> <li>. Material: Diecast aluminum housing</li> <li>. LENS: PC</li> <li>. Housing color: Black</li> <li>. About 50000 hours life time</li> <li>. 1 light 2 functions, white as driving light, amber as fog light/warning light</li> <li>. 3 wires cable/both ends output, white and amber color can be lighted both seperately and together.</li> </ul>	6 PC/ CTN
MD-6017D-180		16.5"180 W		4 PC/ CTN
MD-6017D-240		22"240 W		4 PC/ CTN
MD-6017D-360		33"360 W		4 PC/ CTN
MD-6017D-480		43" 480 W		4 PC/ CTN
MD-6017D-540		48" 540 W		4 PC/ CTN
MD-6017D-600		53" 600 W		2 PC/ CTN
MD-6031-36		4"36 W	<ul style="list-style-type: none"> <li>. 3W each CREE LED</li> <li>. Color temperature:5000K, 6500K</li> <li>. Operation temperature -40°C~60°C</li> <li>. Waterproof rate:IP67</li> <li>. Beam:spot beam, flood beam,combo</li> <li>. Material:diecast aluminum housing</li> <li>. Mounting Bracket:stainless steel bracket.</li> <li>. LENS:PC</li> <li>. Housing color:Black</li> <li>. 3 Wires cable provides high and low beam.</li> </ul>	12PC/ CTN
MD-6031-72		6.5"72 W		8PC/ CTN
MD-6031-108		9"108 W		8PC/ CTN
MD-6031-144		12"144 W		6PC/ CTN
MD-6031-180		15"180 W		4PC/ CTN
MD-6031-216		17"216 W		4PC/ CTN

**MELODY INT'L GROUP LTD**

Tel: +86-750-3329553 Fax:+86-750-6108609

Website: <http://www.melody-lighting.com/>