

MODEL	PICTURE	TYPE	DECCRIPTION	PACKAGING
MD-6017-30		6" 30 W	<ul style="list-style-type: none"> . CREE XML LED 10W/PC . Operating Volt: 10-32Volt DC . Color temperature: 6000K . Operation temperature -40°C~60°C . Waterproof rate: IP67 . Beam:spot beam, flood beam and combo beam . Color: white, amber, white+amber . Material: Diecast aluminum housing . LENS: PC . Housing color: Black . About 50000 hours life time . 1 light 2 functions, white as driving light, amber as fog light/warning light . 3 wires cable/both ends output, white and amber color can be lighted both seperately and together. 	12 PC/ CTN
MD-6017-60		11.5" 60 W		12 PC/ CTN
MD-6017-90		16.5"90 W		12 PC/ CTN
MD-6017-120		22"120 W		6 PC/ CTN
MD-6017-150		27.5"150 W		6 PC/ CTN
MD-6017-180		33"180 W		4 PC/ CTN
MD-6017-210		38"210 W		4 PC/ CTN
MD-6017-240		43" 240 W		4 PC/ CTN
MD-6017-270		48" 270 W		4 PC/ CTN
MD-6017-300		54" 300 W		4 PC/ CTN
MD-6015-30		7" 30W	<ul style="list-style-type: none"> . 5W CREE each LED . Operating Volt: 10-32Volt DC . Color temperature: 6000K . Operation temperature -40°C~60°C . Waterproof rate: IP67 . Beam:spot beam,flood beam and combo beam . Material: Diecast aluminum housing . LENS:PC . Housing color: Black . About 50000 hours life time 	24PC/CTN
MD-6015-60		13" 60W		12PC/CTN
MD-6015-90		20" 90W		12PC/CTN
MD-6015-120		25" 120W		8PC/CTN
MD-6015-150		31" 150W		6PC/CTN
MD-6015-180		38" 180W		6PC/CTN
MD-6015-210		43" 210W		4PC/CTN
MD-6015-240		53" 240W		4PC/CTN

MD-6012-20		5" 20W	<ul style="list-style-type: none"> . 10W each CREE LED . Operating Volt:10-32Volt DC . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam,combo . Material:diecast aluminum housing . Mounting Bracket:stainless steel bracket. . LENS:PC . Housing color:Black,white . EMC compatible 	20PC/CTN
MD-6012-40		8" 40 W		10PC/CTN
MD-6012-60		11" 60 W		10PC/CTN
MD-6012-100		17" 100 W		6PC/CTN
MD-6012-120		20" 120 W		6PC/CTN
MD-6012-180		30"180 W		6PC/CTN
MD-6012-240		40" 240 W		4PC/CTN
MD-6012-260		43" 260 W		4PC/CTN
MD-6012-300		49" 300 W		4PC/CTN
MD-6018-20	    	4.2" 20W	<ul style="list-style-type: none"> . 10W each CREE LED . Operating Volt:10-32Volt DC . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam,flood beam,combo beam . Material:diecast aluminum housing . Mounting Bracket:304 stainless steel bracket,both side bracket and bottom bracket available . LENS:PC . About 50000 hours life time . Housing color: Black 	20PC/CTN
MD-6018-40		7.5" 40W		12PC/CTN
MD-6018-60		10.5" 60W		12PC/CTN
MD-6018-80		13.5" 80W		12PC/CTN
MD-6018-120		20" 120W		6 PC/CTN
MD-6018-140		23" 140W		6 PC/CTN
MD-6018-160		27" 160W		6 PC/CTN
MD-6018-200		32" 200W		6 PC/CTN
MD-6018-260		41" 260W		4 PC/CTN
MD-6018-300		47" 300W		4 PC/CTN
MD-6018-320		50" 320W		4 PC/CTN

MD-6019-9		4.4" 9 W	<ul style="list-style-type: none"> . 3W each CREE LED . Operating Volt:10-32Volt DC . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam,combo . Material:diecast aluminum housing . Mounting Bracket:stainless steel bracket. . LENS:PC . Housing color:Black,white . Both side bracket and bottom bracket available 	20PC/CTN	
MD-6019-18		7.6"18 W		6PC/CTN	
MD-6019-27		10.8"27 W		12PC/CTN	
MD-6019-36		14"36 W		12PC/CTN	
MD-6019-45		17"45 W		12PC/CTN	
MD-6019-54		20.3" 54 W		12PC/CTN	
MD-6019-63				23.5"63 W	12PC/CTN
MD-6019-108				39.5"108 W	9PC/CTN
MD-6019-117				42.6"117 W	9PC/CTN
MD-6019-144				50"144 W	9PC/CTN
MD-6017S-120					22"120 W
MD-6017S-180	33"180 W	4 PC/ CTN			
MD-6017S-210	38" 210 W	4 PC/ CTN			
MD-6017S-240	43" 240 W	4 PC/ CTN			
MD-6017S-270	48.5" 270 W	4 PC/ CTN			
MD-6017S-300	54" 300 W	4 PC/ CTN			