

LED Retrofit Kit Light SS Series

Product Type	Specifications			
	Item	MD-SS-50W	Material:	Fin radiator
	Power	50W	Optional cover	transparent/frosted
	Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
	Luminous Flux	5500-6000LM	Light Color	2700-7000K
	CRI	≥80	Product features	360° rotatable lamp base
	Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
	Power Factor	>0.95	Working Temp	125*200-250mm (Dimension)
	Life span	≥50,000 Hrs	Gross Weight	0.55kg
	Item	MD-SS-60W	Material:	Fin radiator
	Power	60W	Optional cover	transparent/frosted
	Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
	Luminous Flux	6600-7200LM	Light Color	2700-7000K
	CRI	≥80	Product features	360° rotatable lamp base
	Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
	Power Factor	>0.95	Working Temp	125*200-250mm (Dimension)
	Life span	≥50,000 Hrs	Gross Weight	0.55kg
	Item	MD-SS-80W	Material:	Fin radiator
	Power	80W	Optional cover	transparent/frosted
	Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
	Luminous Flux	8800-9600LM	Light Color	2700-7000K
	CRI	≥80	Product features	360° rotatable lamp base
	Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
	Power Factor	>0.95	Working Temp	125*200-250mm (Dimension)
	Life span	≥50,000 Hrs	Gross Weight	0.55kg
	Item	MD-SS-100W	Material:	Fin radiator
	Power	100W	Optional cover	transparent/frosted
	Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
	Luminous Flux	11000-12000LM	Light Color	2700-7000K
	CRI	≥80	Product features	360° rotatable lamp base
	Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
	Power Factor	>0.95	Working Temp	165*230-270mm (Dimension)
	Life span	≥50,000 Hrs	Gross Weight	0.92kg
	Item	MD-SS-120W	Material:	Fin radiator
	Power	120W	Optional cover	transparent/frosted
	Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
	Luminous Flux	13200-14400LM	Light Color	2700-7000K
	CRI	≥80	Product features	360° rotatable lamp base
	Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
	Power Factor	>0.95	Working Temp	165*230-270mm (Dimension)
	Life span	≥50,000 Hrs	Gross Weight	0.92kg



Item	MD-SS-150W	Material:	Fin radiator
Power	150W	Optional cover	transparent/frosted
Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
Luminous Flux	16500-18000LM	Light Color	2700-7000K
CRI	≥80	Product features	360° rotatable lamp base
Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
Power Factor	>0.95	Working Temp	165*230-270mm (Dimension)
Life span	≥50,000 Hrs	Gross Weight	0.92kg



Item	MD-SS-180W	Material:	Fin radiator
Power	180W	Optional cover	transparent/frosted
Input Voltage	AC100-305V	led chip brand	EPISTAR 5730
Luminous Flux	19800-21600LM	Light Color	2700-7000K
CRI	≥80	Product features	360° rotatable lamp base
Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
Power Factor	>0.95	Working Temp	165*230-270mm (Dimension)
Life span	≥50,000 Hrs	Gross Weight	0.92kg



Item	MD-SS-150WB	Material:	Fin radiator
Power	150W	Optional cover	transparent/frosted
Input Voltage	AC100-305V	led chip brand	CREE XTE
Luminous Flux	15750-17250LM	Light Color	2700-7000K
CRI	≥80	Product features	360° rotatable lamp base
Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
Power Factor	>0.95	Working Temp	165*230-270mm (Dimension)
Life span	≥50,000 Hrs	Gross Weight	0.92kg



Item	MD-SS-180WB	Material:	Fin radiator
Power	180W	Optional cover	transparent/frosted
Input Voltage	AC100-305V	led chip brand	CREE XTE
Luminous Flux	18900-20700LM	Light Color	2700-7000K
CRI	≥80	Product features	360° rotatable lamp base
Frequency range	50Hz-60Hz	lamp base	E26/E27/E39/40/Hanging
Power Factor	>0.95	Working Temp	165*230-270mm (Dimension)
Life span	≥50,000 Hrs	Gross Weight	0.92kg