











LED Wall Pack Lamp

Product Type	Specifications				Drawing
	Item	MD-BL-40W	Luminous Flux	3600~3960LM	
	Power	40W	CRI	≥80	
	Power Efficiency	>87 %	led chip brand	PHILIPS 3030	
	Input Voltage	AC100-305V	Light Color	2700-7000K	
	Frequency range	50Hz-60Hz	Beam Angle	120°	
	Power Factor	>0.95	IP Grade	IP65	
	Life span	≥50,000 Hrs	Size	363*230*195mm	
	Material	Aluminum Alloy	Gross Weight	5.5KG	
	Item	MD-BL-50w	Luminous Flux	4600-4800LM	
	Power	50W	CRI	≥80	
	Power Efficiency	>87 %	led chip brand	PHILIPS 3030	
	Input Voltage	AC100-305V	Light Color	2700-7000K	
	Frequency range	50Hz-60Hz	Beam Angle	120°	
	Power Factor	>0.95	IP Grade	IP65	
	Life span	≥50,000 Hrs	Size	363*230*195mm	
	Material	Aluminum Alloy	Gross Weight	5.5KG	
	Item	MD-BL-60w	Luminous Flux	5200-5400LM	
	Power	60W	CRI	≥80	
	Power Efficiency	>87 %	led chip brand	PHILIPS 3030	
	Input Voltage	AC100-305V	Light Color	2700-7000K	
	Frequency range	50Hz-60Hz	Beam Angle	120°	
	Power Factor	>0.95	IP Grade	IP65	
	Life span	≥50,000 Hrs	Size	363*230*195mm	
	Material	Aluminum Alloy	Gross Weight	5.5KG	
	Item	MD-BL-80W	Luminous Flux	7000~7200LM	
	Power	80W	CRI	≥80	
	Power Efficiency	>87 %	led chip brand	PHILIPS 3030	
	Input Voltage	AC100-305V	Light Color	2700-7000K	
	Frequency range	50Hz-60Hz	Beam Angle	120°	
	Power Factor	>0.95	IP Grade	IP65	
	Life span	≥50,000 Hrs	Size	363*230*195mm	
	Material	Aluminum Alloy	Gross Weight	5.5KG	
	Item	MD-BL-100W	Luminous Flux	8000~8500LM	
	Power	100W	CRI	≥80	
	Power Efficiency	>87 %	led chip brand	PHILIPS 3030	
	Input Voltage	AC100-305V	Light Color	2700-7000K	
	Frequency range	50Hz-60Hz	Beam Angle	120°	
	Power Factor	>0.95	IP Grade	IP65	
	Life span	≥50,000 Hrs	Size	363*230*195mm	
	Material	Aluminum Alloy	Gross Weight	5.8KG	



Item	MD-BL-120W	Luminous Flux	96000~10000LM
Power	120W	CRI	≥80
Power Efficiency	>87 %	led chip brand	PHILIPS 3030
Input Voltage	AC100-305V	Light Color	2700-7000K
Frequency range	50Hz-60Hz	Beam Angle	120°
Power Factor	>0.95	IP Grade	IP65
Life span	≥50,000 Hrs	Size	363*230*195mm
Material	Aluminum Alloy	Gross Weight	6KG

