

MODEL	PICTURE	TYPE	DECCRIPTION	PACKAGING
MD-6081-18		3"18 W	<ul style="list-style-type: none"> . LED Power:18Watt Epistar LED 3W/PC . Operating Volt:10-40Volt DC . Light output about 1500 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50000 hours life time . Size:76mm*42mm*90mm 	80 PC/CTN MEAS: 64*36*21CM N.W/G.W: 24/25KG
MD-6081-27		4.25"27W	<ul style="list-style-type: none"> . LED Power:27Watt CREE LED 3W/PC . Operating Volt:10-40Volt DC . Light output about: 2400 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:106mm*106mm*75mm 	20 PC/CTN MEAS: 41.5*25*32CM N.W/G.W:18.5/19.51KG
MD-6081-40A		4.25"40Watt	<ul style="list-style-type: none"> . LED Power:40Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Light output about: 3500 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:108mm*72mm*117mm 	20 PC/CTN MEAS: 41.5*25*32CM N.W/G.W:18.5/19.51KG
MD-6081-40B		5.5"40 Watt	<ul style="list-style-type: none"> . LED Power:40Watt CREE LED 5W/PC . Operating Volt:10-40Volt DC . Light output about 3500 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:140mm*78mm*113mm 	16 PC/CTN MEAS:66*29.5*23CM N.W/G.W:15/16KG

MD-6081-50		5"50Watt	<ul style="list-style-type: none"> . LED Power:50Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Light output about 4200 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . 60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:125mm*103mm*118mm 	12PC/CTN MEAS:53*35.5*29CM N.W/G.W:19/20KG
MD-6081-60		5"60W	<ul style="list-style-type: none"> . LED Power:60Watt CREE LED 5W/PC . Operating Volt:10-40Volt DC . Light output about: 5000 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:125mm*103mm*118mm 	12PC/CTN MEAS:53*35.5*29CM N.W/G.W:19/20KG
MD-6081-90		6"90 W	<ul style="list-style-type: none"> . LED Power:90Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Light output about 7050 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:152mm*115mm*141mm 	8PC/CTN MEAS:40.2*40.2*35CM N.W/G.W:20.6/27.6KG

<p>MD-6081-100</p>		<p>6"100 W</p>	<ul style="list-style-type: none"> . LED Power:100Watt CREE LED 5W/PC . Operating Volt:10-40Volt DC . Light output about: 8200 lumen . Color temperature:6000K . Operation temperature -40°C~80°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time . Size:152mm*115mm*141mm 	<p>8PC/CTN MEAS:40.2*40.2*35CM N.W/G.W:20.6/27.6KG</p>
<p>MD-6081-120</p>		<p>7.4"120 W</p>	<ul style="list-style-type: none"> . LED Power: 120Watt CREE LED Each 10W/PC . Operating Volt: 10-80Volt DC . Light output about 10,800 lumen . Color temperature: 6300K . Operation temperature -45°C~85°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam . Material: Diecast aluminum housing . LENS: PC . Housing color: Black . About 50000 hours life time . Size: 178*167*135mm 	<p>4PC/CTN MEAS:50*48.5*38CM N.W/G.W:16.5/17.5KG</p>
<p>MD-6157</p>		<p>3"15 Watt</p>	<ul style="list-style-type: none"> . LED Power:15Watt Cree LED 15W/PC . Operating Volt:10-60Volt DC . Light output about 1500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot ,flood . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 50000 hours life time . Size:75*90*80mm 	<p>20PC/CTN MEAS:66*30*23.5CM N.W/G.W:11.6/12.6KG</p>

<p>MD-6302</p>		<p>5.5"30 Watt</p>	<ul style="list-style-type: none"> . LED Power:15Watt Cree LED 15W/PC . Operating Volt:10-60Volt DC . Light output about 3000 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot ,flood . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 50000 hours life time . Size:140*119*95mm 	<p>12PC/CTN MEAS:44*35.5*32CM N.W/G.W:12/13KG</p>
<p>MD-6105</p>		<p>4"10 Watt</p>	<ul style="list-style-type: none"> . LED Power:10Watt CREE LED 5W/PC . Color: Blue, White . Operating Volt: 10-60 Volt DC . Light output about 1000 lumen . Color temperature: 6000K . Operation temperature -40°C~+105°C . Waterproof rate: IP67 . Beam: 30° spot beam,60° flood beam . Material: Diecast aluminum housing,S304 stainless steel bracket . LENS:convex lens . Housing color: Black . About 50000 hours life time 	<p>12PC/CTN MEAS:44*35.5*32CM N.W/G.W:12/13KG</p>
<p>MD-6105R 4"</p>		<p>10 Watt</p>	<ul style="list-style-type: none"> . LED Power:10Watt CREE LED 5W/PC . Color: White . Operating Volt: 10-60 Volt DC . Light output about 1000 lumen . Color temperature: 6000K . Operation temperature -40°C~+105°C . Waterproof rate: IP67 . Beam: 5° spot beam . Material: Diecast aluminum housing,S304 stainless steel bracket . LENS:convex lens . Housing color: Black . About 50000 hours life time 	<p>20PC/CTN</p>

<p>MD-6205 4" White Forklift light</p>		<p>20 Watt</p>	<ul style="list-style-type: none"> . LED Power:10Watt CREE LED 5W/PC . Color: Blue, White . Operating Volt: 10-60 Volt DC . Light output about 1000 lumen . Color temperature: 6000K . Operation temperature -40°C~+105°C . Waterproof rate: IP67 . Beam: flood beam, spot beam . Material: Diecast aluminum housing,S304 stainless steel bracket . Housing color: Black . About 50000 hours life time . Size: 98*76.5*75mm 	<p>20PC/CTN</p>
<p>MD-6101 2"</p> 	 <p>grapped bracket available, price extra \$2.0 DT connector available, price extra \$1.5</p>	<p>10 Watt</p>	<ul style="list-style-type: none"> . LED Power:10Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Light output about 800 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:90°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black,White,chrome . About 50,000 hours life time . Size:52mm*52mm*63mm 	<p>20 PC/CTN MEAS: 55*26.8*16CM N.W/G.W: 7.57/9.6KG</p>
<p>MD-6102 2"</p> 	 <p>grapped bracket available, price extra \$2.0 DT connector available, price extra \$1.5</p>	<p>10 Watt</p>	<ul style="list-style-type: none"> . LED Power:10Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Light output about 800 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:90°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black,White,Chrome . About 50,000 hours life time . Size:55mm*55mm*65mm 	<p>20 PC/CTN MEAS: 54*24*15CM N.W/G.W: 5/6.66KG</p>

<p>MD-6121</p>		<p>12Watt</p>	<ul style="list-style-type: none"> . LED Power: 12Watt Epistar LED 3W/PC . Operating Volt: 10-30Volt DC . Light output about 900 lumen . Color temperature: 6000K . Operation temperature -40°C~60°C . Waterproof rate: IP67 . Beam: 60°flood beam . Material: Diecast aluminum housing, stainless steel bracket . LENS: PMMA LENS . Housing color: Black, White . About 30,000 hours life time 	<p>20 PC/CTN MEAS: 48*28*22CM N.W/G.W: 10/11KG</p>
<p>MD-6122 2.5"</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power: 12Watt Epistar LED EACH 3W/PC . Operating Volt: 10-30Volt DC . Light output about 950 lumen . Color temperature: 6000K . Operation temperature -40°C~60°C . Waterproof rate: IP67 . Beam: 60°flood beam, 30°spot beam optional . Material: diecast aluminum housing, stainless steel bracket . LENS: Toughened glass . Housing color: Black, White . About 30000 hours life time . Size: 66mm*66mm*65mm 	<p>20 PC/CTN MEAS: 47.5*26.5*18.5CM N.W/G.W: 8/10KG</p>
<p>MD-6125 3" Without color covers</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power: 12Watt Cree LED 3W/PC . Operating Volt: 10-30Volt DC . Light output about 900 lumen . Color temperature: 6000K . Operation temperature -40°C~60°C . Waterproof rate: IP67 . Beam: spot beam, flood beam . Material: diecast aluminum housing, stainless steel bracket . LENS: PC . Housing color: Black, White . About 50,000 hours life time 	<p>18 PC/CTN MEAS: 32.8*23*40CM N.W/G.W: 13.5/15KG</p>

<p>MD-6203A 3" Without color covers</p>		<p>20 Watt</p>	<ul style="list-style-type: none"> . LED Power:20Watt Cree LED 5W/PC . Operating Volt:10-30Volt DC . Light output about 1500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam,flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black,White . About 50,000 hours life time . Size:83mm*65mm*120mm . Clear, yellow, red,blue color covers available. 	<p>18 PC/CTN MEAS: 32.8*23*40CM N.W/G.W: 13.5/15KG</p>
<p>MD-6129 6" Marine light</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power:12Watt Epistar LED 3W/PC . Operating Volt:10-30Volt DC . 4pc*3w CREE LED . Light output about 900 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:flood beam . Material:diecast aluminum housing . Mounting Bracket:stainless steel bracket. . LENS:PC . Housing color:Black . About 30,000 hours life time 	<p>20PC/CTN</p>
<p>agriculture light MD-6043A- 12W 5.5"</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power:12Watt CREE LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 850 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam . Material:diecast aluminum housing . LENS:PC . Housing color:Black . Size:138mm*50mm*80mm 	<p>20PCS/CTN BOX SIZE: 18*9*8cm G.W:0.45KG/BOX</p>

<p>agriculture light MD-6043B- 12W 5.5"</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power:12Watt CREE LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 850 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . Size:138mm*50mm*80mm 	<p>20PCS/CTN BOX SIZE: 18*9*8cm G.W:0.45KG/BOX</p>
<p>agriculture light MD-6043B- 20W 5.5"</p>		<p>20 Watt</p>	<ul style="list-style-type: none"> . LED Power:20Watt CREE LED Each 5W/PC . Operating Volt:10-60Volt DC . Light output about 1450 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . Size:138mm*50mm*80mm 	<p>20PCS/CTN BOX SIZE: 18*9*8cm G.W:0.5KG/BOX</p>
<p>agriculture light MD-6044 5.3"</p>		<p>18 Watt</p>	<ul style="list-style-type: none"> . LED Power:18Watt CREE LED Each 3W/PC . Operating Volt:10-60Volt DC . Light output about 6000 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . Size:134mm*134mm*100mm 	<p>1 PC/ BOX</p>

<p>MD-6044B 5.3"</p>		<p>18 Watt</p>	<ul style="list-style-type: none"> . LED Power:18Watt CREE LED Each 3W/PC . Operating Volt:10-60Volt DC . Light output about 1800 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . Size:134mm*134mm*100mm 	<p>1 PC/ BOX</p>
<p>Hot MD-6125FC 3"</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power:12Watt CREE LED 3W/PC . Flush Mount . Operating Volt:10-30Volt DC . Light output about 900 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam,flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time 	<p>20 PC/CTN MEAS: 32.5*27.5*62CM N.W/G.W: 14/16KG</p>
<p>Hot MD-6186 3"</p>		<p>18 Watt</p>	<ul style="list-style-type: none"> . LED Power:18Watt Cree LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 1500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:flood beam,spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 30000 hours life time . Size:80mm*80mm*85mm . Clear, yellow, red,blue color covers availble. 	<p>18 PC/CTN MEAS: 33*23*40CM N.W/G.W: 13/14KG</p>

<p>Hot MD-6186FC 3"</p>		<p>18 Watt</p>	<ul style="list-style-type: none"> . LED Power:18Watt Epistar LED 3W/PC . Flush Mount . Operating Volt:10-30Volt DC . Light output about 1500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:flood beam,spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 50,000 hours life time 	<p>20 PC/CTN MEAS: 32.5*27.5*62CM N.W/G.W: 14/16KG</p>
<p>Hot MD-6152 5.5"</p>		<p>15 Watt</p>	<ul style="list-style-type: none"> . LED Power:15Watt Epistar LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 1150 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam,flood beam . Material:diecast aluminum housing,stainless steel bracket. . LENS:Toughened glass . Housing color:Black,White . About 30000 hours life time . Size:145mm*76mm*45mm 	<p>20 PC/CTN MEAS: 42*21*22CM N.W/G.W: 11/13KG</p>
<p>New MD-6183 6"</p>		<p>18 Watt</p>	<ul style="list-style-type: none"> . LED Power:18Watt Epistar LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 1500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam,flood beam . Material:diecast aluminum housing,stainless steel bracket. . LENS:PC . Housing color:Black,White . About 30000 hours life time . Size:145mm*76mm*45mm 	<p>20 PC/CTN MEAS: 42.2*20*47.5CM N.W/G.W: 11/13KG</p>

<p>New MD-6201 4"</p>		<p>20 Watt</p>	<ul style="list-style-type: none"> . LED Power:20Watt CREE LED EACH 1W/PC . Operating Volt:10-30Volt DC . Light output about 2000 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC LENS . Housing color:Black,White . About 30000 hours life time . Size: 105*105*90mm 	<p>20 PC/CTN MEAS: 48*23*32CM N.W/G.W: 17/19KG</p>
<p>MD-6251 4"</p>		<p>25 Watt</p>	<ul style="list-style-type: none"> . LED Power:25Watt CREE LED EACH 1W/PC . Operating Volt:10-30Volt DC . Light output about 2500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC Lens . Housing color:Black,White . About 30000 hours life time . Size:106mm*70mm*106mm 	<p>20 PC/CTN MEAS: 48*23*32CM N.W/G.W: 22/23KG</p>
<p>MD-6155 4"</p>		<p>15 Watt</p>	<ul style="list-style-type: none"> . LED Power:15Watt LED EACH 3W/PC . Operating Volt:10-30Volt DC . Light output about 1300 lumen . Color temperature:6500K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam,flood beam optional . Material:diecast aluminum alloy housing . LENS:PMMA LENS . Housing color:Black . About 30000 hours life time . Size:110mm*41mm*110mm <p>Note: CREE chips available,MOQ:100pcs,price Extra \$1.5/pc</p>	<p>20 PC/CTN MEAS: 35*33.4*27CM N.W/G.W: 15/17KG</p>

<p>MD-6185 4"</p>		<p>18 Watt Epistar</p>	<ul style="list-style-type: none"> . LED Power:18Watt LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 1500 lumen . Color temperature:6500K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam . Material:diecast aluminum alloy housing . LENS:PMMA LENS . Housing color:Black,white . About 30,000 hours life time . Size:115mm*115mm*85mm 	<p>20 PC/CTN MEAS: 35.5*33.0*26.5CM N.W/G.W: 15/16KG</p>
<p>MD-6241 4"</p>		<p>24 Watt Epistar</p>	<ul style="list-style-type: none"> . LED Power:24Watt LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 1850 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam . Material:diecast aluminum housing . Mounting Bracket:stainless steel bracket . LENS:PMMA LENS . Housing color:Black . About 30000 hours life time . Size:110mm*51mm*135mm 	<p>20 PC/CTN MEAS: 35*32*26CM N.W/G.W: 14/15KG</p>
<p>MD-6242 4"</p>		<p>24 Watt Epistar</p>	<ul style="list-style-type: none"> . LED Power:24Watt LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 1850 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam . Material:diecast aluminum housing . Mounting Bracket:stainless steel bracket . LENS:PMMA LENS . Housing color:Black . About 30000 hours life time . Size:110mm*51mm*135mm 	<p>20 PC/CTN MEAS: 35*32*26CM N.W/G.W: 14/15KG</p>

<p>MD-6271 4"</p>		<p>27 Watt Epistar</p>	<ul style="list-style-type: none"> . LED Power:27Watt LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 2500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam, 30°spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC LENS . Housing color:Black . About 30000 hours life time . Size:110mm*62mm*135mm 	<p>20 PC/CTN MEAS: 35*32*26CM N.W/G.W: 17/18KG</p>
<p>MD-6272 4"</p>		<p>27 Watt Epistar</p>	<ul style="list-style-type: none"> . LED Power:27Watt LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 2500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam, 30°spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC LENS . Housing color:Black . About 30000 hours life time . Size:116mm*63mm*135mm 	<p>20 PC/CTN MEAS: 35*32*26CM N.W/G.W: 18/19KG</p>
<p>MD-6273 5.5"</p>		<p>27 Watt</p>	<ul style="list-style-type: none"> . LED Power:27Watt CREE LED EACH 3W/PC . Operating Volt:10-30Volt DC . Light output about 2400 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: 90°flood beam,30°spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC LENS . Housing color:Black . About 30000 hours life time . Size:147mm*73mm*150mm 	<p>12 PC/CTN MEAS: 48*32*36CM N.W/G.W: 14/16KG</p>

<p>MD-6365 6.5"</p>		<p>36 Watt</p>	<ul style="list-style-type: none"> . LED Power:36Watt CREE LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 3400 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:90°flood beam,30°spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC LENS . Housing color:Black, Silver . About 30000 hours life time . Size:175mm*77mm*157mm 	<p>12 PC/CTN MEAS: 48*32*40CM N.W/G.W: 17/19KG</p>
<p>MD-6054H 5.5"</p>		<p>36 Watt</p>	<ul style="list-style-type: none"> . LED Power:36Watt Epistar LED Each 3W/PC . Operating Volt:10-30Volt DC . Light output about 2600 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 30000 hours life time . Size:145mm*70mm*145mm . With waterproof on /off switch and handle. 	<p>20PC/CTN</p>
<p>MD-6402 5"</p>		<p>40 Watt</p>	<ul style="list-style-type: none"> . LED Power:40Watt CREE LED 10W/PC . Operating Volt:10-30Volt DC . Light output about 3500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing, stainless steel bracket . LENS:Toughened glass . Housing color:Black . About 30000 hours life time . Size:127mm*90mm*160mm 	<p>12 PC/CTN MEAS: 58*31*25 CM N.W/G.W: 20/22KG</p>

<p>MD-6482 5"</p>		<p>48 Watt</p>	<ul style="list-style-type: none"> . LED Power:48Watt CREE LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 3800 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:toughened glass . Housing color:Black . Size:127mm*90mm*160mm 	<p>12 PC/CTN MEAS: 58*31*25CM N.W/G.W: 20/22KG</p>
<p>Hot MD-6481 4.5"</p>		<p>48 Watt</p>	<ul style="list-style-type: none"> . LED Power:48Watt Epistar LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 3500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PMMA LENS . Housing color:Black . About 30000 hours life time . Size:110mm*72mm*110mm 	<p>20 PC/CTN MEAS: 32.7*29*47CM N.W/G.W: 22/24KG</p>
<p>MD-6451 6"</p>		<p>45 Watt</p>	<ul style="list-style-type: none"> . LED Power:45Watt Epistar LED EACH 3W/PC . Operating Volt:10-30Volt DC . Light output about 3900 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam, flood beam . Material:diecast aluminum housing,stainless steel bracket . LENS:Toughened glass . Housing color:Black . About 30000 hours life time . Size:110mm*72mm*110mm 	<p>12 PC/CTN MEAS: 40*36*31CM N.W/G.W: 17/18KG</p>

<p>MD-6601 5.2"</p>		<p>60 Watt</p>	<ul style="list-style-type: none"> . LED Power:10Watt CREE LED 10W/PC . Operating Volt:10-30Volt DC . Light output about 6000 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:90°flood beam,10°spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black . About 30000 hours life time . Size:144mm*78mm*94mm 	<p>8pc/box MEAS:43*37.5*36CM N.W/G.W: 22/24KGS</p>
<p>MD-6051-45 5.5"</p>		<p>45 Watt</p>	<ul style="list-style-type: none"> . LED Power:45Watt CREE LED 5W/PC . Operating Volt:10-60Volt DC . Light output about 3800 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:flood beam,spot beam optional . Material:diecast aluminum housing,stainless steel bracket,2 WAY FOR INSTALL . LENS:PC . Housing color:Black . Size:140mm*140mm*169mm 	<p>12 PC/ CTN MEAS:50.5*46*25CM N.W/G.W: 21/22KG</p>
<p>MD-6051-60 7"</p>		<p>60 Watt</p>	<ul style="list-style-type: none"> . LED Power:60Watt CREE LED 5W/PC . Operating Volt:10-60Volt DC . Light output about 5100 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:flood beam,spot beam optional . Material:diecast aluminum housing,stainless steel bracket,2 functions brackets . LENS:PC . Housing color:Black . Size:180mm*180mm*207mm 	<p>1 PC/ BOX,8PCS/CTN Box size:22.5*23.2*10.5CM MEAS:53.5*42*26.5CM M N.W/G.W:18/20KG</p>

<p>MD-6403 5"</p>		<p>40 Watt</p>	<ul style="list-style-type: none"> . LED Power:40Watt CREE LED 10W/PC . Operating Volt:10-30Volt DC . Light output about 3500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam optional . Material:diecast aluminum housing,stainless steel bracket . LENS:Toughened glass . Housing color:Black . About 30000 hours life time . Size:127mm*90mm*160mm 	<p>12 PC/CTN MEAS:48*38*30CM N.W/G.W: 15/17KG</p>
<p>MD-6701 6"</p>		<p>70 Watt</p>	<ul style="list-style-type: none"> . LED Power:70Watt Cree, LED Each 10W/PC . Operating Volt:10-30Volt DC . Light output about 5600 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot,flood,combo . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 30000 hours life time . Size:155mm*102mm*155mm 	<p>8PCS/ CTN MEAS: 48*38*30CM N/G.W:12/13.5KG</p>
<p>MD-6801 5.5"</p>		<p>80 Watt</p>	<ul style="list-style-type: none"> . LED Power:80Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Lumen: 7200 . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: flood beam, spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black 	<p>1 PC/ BOX,8PCS/CTN MEAS:53.5*42*26.5CM M N.W/G.W:16/18KGS</p>

<p>MD-6502 4"</p>		<p>50 Watt</p>	<ul style="list-style-type: none"> . LED Power:50Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Lumen: 4500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:flood beam,spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black 	<p>1 PC/ BOX</p>
<p>MD-6511 7"</p>		<p>51 Watt</p>	<ul style="list-style-type: none"> . LED Power:51Watt Epistar LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 3700 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam,30°spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Ring color:Red,Black . Size:160mm*86mm*202mm Handal available, price extra \$3.0,swival bracket available,price \$1.5 	<p>6 PC/CTN MEAS: 46*25*37CM N/G.W:15/16KG</p>
<p>MD-6400 6.5"</p>		<p>40 Watt</p>	<ul style="list-style-type: none"> . LED Power:40Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Lumen: 3600 . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:10 spot beam . Material:diecast aluminum housing,stainless steel bracket . LENS:PC . Housing color:Black,White . Size:168mm*68mm*117mm 	<p>1 PC/ BOX</p>

<p>MD-6600 7"</p>		<p>60 Watt</p>	<ul style="list-style-type: none"> . LED Power:60Watt CREE LED 10W/PC . Operating Volt:10-60Volt DC . Lumen: 5400 . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:10 spot beam . Material:diecast aluminum housing, stainless steel bracket . LENS:PC . Housing color:Black, White . Size:180mm*88mm*135mm 	<p>1 PC/ BOX</p>
<p>MD-6053 5.5" I Generation</p>		<p>45 Watt</p>	<ul style="list-style-type: none"> . LED Power:45Watt Epistar LED Each 3W/PC . Operating Volt:10-30Volt DC . Light output about 3200 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:hi-low beam in one . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 30000 hours life time . Size:168mm*78mm*109mm 	<p>2 PC/ BOX,24PCS/CTN MEAS:52.5*40*30 N/G.W:17/18KG</p>
<p>MD-6053R 5.5" II Generation</p>		<p>45 Watt</p>	<ul style="list-style-type: none"> . LED Power:45Watt Epistar LED Each 3W/PC . Operating Volt:10-30Volt DC . Light output about 3200 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:hi-low beam in one . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 30000 hours life time . Size:168mm*78mm*109mm <p>Note: 2 functions with 2 different mounting methods (either headlight or work lights)</p>	<p>12PCS/CTN MEAS:41.7*38*33CM N/G.W:17/18KG</p>




<p>MD-6054 5.5" I Generation</p>		<p>36 Watt</p>	<ul style="list-style-type: none"> . LED Power:36Watt Epistar LED 3W/PC . Operating Volt:10-30Volt DC . Light output about 2600 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:sot beam . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 30000 hours life time . Size:145mm*70mm*145mm 	<p>2 PC/ BOX,24PCS/CTN MEAS:53*32.5*32CM N/G.W:13/15KG</p>
<p>MD-6052- 12W</p>		<p>12 Watt</p>	<ul style="list-style-type: none"> . LED Power:12Watt Epistar LED EACH 3W/PC . Operating Volt:10-30Volt DC . Light output about 800 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:60°flood beam . Material:diecast aluminum housing,304 stainless steel bracket . LENS:PC LENS . Housing color:Black,White . About 30000 hours life time . Size:80mm*80m*45mm 	<p>40 PC/CTN MEAS:46.5*27.5*21.5 CM N.W/G.W: 14/16KG</p>
<p>MD-6041 4"</p>		<p>24Watt</p>	<ul style="list-style-type: none"> . LED Power: 24Watt EPISTAR LED Each 3W/PC . Operating Volt: 10-30Volt DC . Light output about 1900 lumen . Color temperature: 6300K . Operation temperature -45°C~85°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam . Material: Diecast aluminum housing . LENS: PC . Housing color: Black . About 30000 hours life time 	<p>20 PC/CTN MEAS: 58*31*25CM N.W/G.W: 17/20.5KG</p>

<p>MD-6042 4"</p>		<p>21 Watt</p>	<ul style="list-style-type: none"> . LED Power: 21Watt EPISTAR LED Each 3W/PC . Operating Volt: 10-30Volt DC . Light output about 1600 lumen . Color temperature: 6300K . Operation temperature -45°C~85°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam . Material: Diecast aluminum housing . LENS: PC . Housing color: Black . About 30000 hours life time 	<p>20PC/CTN</p>
<p>MD-2109 7" wireless remote lights</p>		<p>50 Watt</p>	<ul style="list-style-type: none"> . LED Power:50Watt CREE LED EACH 5W/PC . Operating Volt:10-30Volt DC . Light output about 5000 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam:spot beam . Material:Housing: Hi-impact nylon Plastic, Aluminum diecast reflector with magnet base,Lens: Toughened glass . Housing color:Black, white . About 30000 hours life time . Size:185mm*150mm*230mm 200m Wireless Remote with 360 deg horizontal and 120 deg vertical swival 	<p>4 PCS/CTN MEAS: 52*31*52.5CM N.W/G.W: 14/16 KGS</p>
<p>New MD-4709 5" 10W LED Searchlight</p>		<p>10 Watt</p>	<ul style="list-style-type: none"> .LED Power:10Watt, 1pcs 10W CREE LED .Operating Volt:9-32volt DC .Beam: Spot beam .Color temperature:6000K .Operation temperature -40°C~150°C .LENS:PMMA LENS .Housing color:Black . Waterproof rate:IP67 .About 50,000 hours life time .Lighting Distance:over 1km 	<p>QTY:8PC/CTN Meas:46*46*28cm N.W/G.W: 5.5KG/9.6KG</p>

MELODY INT'L GROUP LTD

Tel: +86-750-3329553 Fax:+86-750-6108609

Website: <http://www.melody-lighting.com/>

MODEL	PICTURE	TYPE	DECCRIPTION	PACKAGING
New MD-6062-60 5"		60 Watt	<ul style="list-style-type: none"> . LED Power: 60Watt CREE LED 10W/PC . Operating Volt:10-30Volt DC . Light output about 5100 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing, stainless steel bracket, 2 functions brackets . LENS:PC . Housing color:Black 	12PC/CTN MEAS: 46.5*40*26.5CM N.W/G.W: 16/17KG
New MD-6062-90 7"		90 Watt	<ul style="list-style-type: none"> . LED Power: 90Watt CREE LED 5W/PC . Operating Volt:10-30Volt DC . Light output about 7650 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing, stainless steel bracket, 2 functions brackets . LENS:PC . Housing color:Black 	8 PC/ CTN MEAS:47.8*43*28.5CM N.W/G.W: 21/22KG
New MD-6062-90 7"		90 Watt	<ul style="list-style-type: none"> . LED Power: 90Watt CREE LED 10W/PC . Operating Volt:10-30Volt DC . Light output about 7650 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing, stainless steel bracket, 2 functions brackets . LENS:PC . Housing color:Black 	8 PC/ CTN MEAS:47.8*43*28.5CM N.W/G.W: 21/22KG

<p>New MD-6062- 120 9"</p>		<p>120 Watt</p>	<ul style="list-style-type: none"> . LED Power: 120Watt CREE LED 10W/PC . Operating Volt:10-30Volt DC . Light output about 10000 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing,stainless steel bracket,2 functions brackets . LENS:PC . Housing color:Black 	<p>4 PC/CTN MEAS:51.4*43*28.5CM N.W/G.W: 15/17KG</p>
<p>New MD-6062- 150 9"</p>		<p>150 Watt</p>	<ul style="list-style-type: none"> . LED Power: 150Watt CREE LED 5W/PC . Operating Volt:10-30Volt DC . Light output about 12500 lumen . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Beam: spot beam . Material:diecast aluminum housing,stainless steel bracket,2 functions brackets . LENS:PC . Housing color:Black 	<p>4 PC/CTN MEAS:51.4*43*28.5CM N.W/G.W: 15/17KG</p>
<p>MD-6071 7"</p>		<p>70 Watt</p>	<ul style="list-style-type: none"> . LED Power:55Watt on low beam, 70Watt on high beam . Operating Volt:10-36Volt DC . Light output: 3850 lumen for low beam,4900 lumen for high beam . Color temperature:6000K . Operation temperature -40°C~60°C . Waterproof rate:IP67 . Connector: H4 to H13 converter . Beam:hi-low beam in one . Material:diecast aluminum housing . LENS:PC . Housing color:Black . About 50000 hours life time 	<p>8 PC/ CTN</p>

MD-6072
7"



85 Watt

- . LED Power:70Watt on low beam, 85Watt on high beam
- . Operating Volt:10-36Volt DC
- . Light output: 4900 lumen for low beam,5950 lumen for high beam
- . Color temperature:6000K
- . Operation temperature -40°C~60°C
- . Waterproof rate:IP67
- . Connector: H4 to H13 converter
- . Beam:hi-low beam in one
- . Material:diecast aluminum housing
- . LENS:PC
- . Housing color:Black
- . About 50000 hours life time

8 PC/ CTN

MELODY INT'L GROUP LTD

Tel: +86-750-3329553 Fax:+86-750-6108609

Website: <http://www.melody-lighting.com/>