



Picture	Item Number	Specification
	MD-MR11-1WYH	Power:1W AC/DC12V Size $\Phi 35 \times 40$ mm Beam angle:60° Base:GU4 3000K/4000K/6000K
	MD-MR11-3WYH	Power:3W AC/DC12V 110V/220V Size $\Phi 35 \times 40$ mm Beam angle:45° Base:GU4 3000K/4000K/6000K
	MD-MR11-2.5WLN	Power:2.5W AC/DC12V Size $\Phi 35 \times 37$ mm Beam angle:30°120° Base:GU4 3000K/4000K/6000K
	MD-MR11-4WLN	Power:4W AC/DC12V Size $\Phi 35 \times 41$ mm Beam angle:30°120° Base:GU4 3000K/4000K/6000K



MD-MR16-5WBE

Power:5W
AC/DC12V
Size $\Phi 50 \times 51$ mm
Beam angle:38°
Base:GU5.3
3000K/4000K/6000K



MD-GU10-5WBE

Power:5W
AC100-240V
Size $\Phi 50 \times 56$ mm
Beam angle:38°
Base:GU10
3000K/4000K/6000K



MD-MR16-6WBA

Power:6W
AC/DC12V
Size $\Phi 50 \times 52$ mm
Beam angle:38°
Base:GU5.3
3000K/4000K/6000K



MD-GU10-6WBA

Power:6W
AC100-240V
Size $\Phi 50 \times 52$ mm
Beam angle:38°
Base:GU10
3000K/4000K/6000K



MD-MR16-6WAS

Power:6W
AC/DC12V
Size $\Phi 50 \times 60 \text{mm}$
Beam angle:15° 24° 36°
Base:GU5.3
3000K/4000K/6000K



MD-MR16-6WAS

Power:6W
220V AC 110V
Size $\Phi 50 \times 60 \text{mm}$
Beam angle:15° 24° 36°
Base:GU5.3
3000K/4000K/6000K



MD-GU10-6WAS

Power:6W
AC 100-240V
Size $\Phi 50 \times 60 \text{mm}$
Beam angle:15° 24° 36°
Base:GU10
3000K/4000K/6000K



MD-MR16-6WFB

Power:6W
AC/DC12V
Size $\Phi 50 \times 70 \text{mm}$
Beam angle:38°/60°
Base:GU5.3
3000K/4000K/6000K



MD-GU10-6WFB

Power:6W
AC100-240V
Size $\Phi 50 \times 76 \text{mm}$
Beam angle:38°/60°
Base:GU10
3000K/4000K/6000K



MD-MR16-9WBE

Power:9W
AC/DC12V
Size $\Phi 50 \times 80 \text{mm}$
Beam angle:38°/60°
Base:GU5.3
3000K/4000K/6000K



MD-GU10-9WBE

Power:9W
AC100-240V
Size $\Phi 50 \times 86 \text{mm}$
Beam angle:38°/60°
Base:GU10
3000K/4000K/6000K



MD-PAR20-10WO

Base:E27/E26
Power:10W
AC220V
Beam angle:15°24° 36°
Size: $\phi 64 \times 95$
CCT: 3000K /4000K /6000K



MD-PAR30-40WA

Base:E27/E26/G12
Power:40W
AC100-240V
Beam angle:24° 36°100°
Size: φ90*120
CCT: 3000K /4000K /6000K



MD-PAR30-40WA

Base:E27/E26/G12
Power:40W
AC100-240V
Beam angle:24° 36°100°
Size: φ90*120
CCT: 3000K /4000K /6000K



MD-PAR30-30WO

Base:E27/E26
Power:30W
AC220V
Beam angle:15°24°36°
Size: φ95*120
CCT: 3000K /4000K /6000K



MD-PAR38-40WO

Base:E27/E26
Power:40W
AC220V
Beam angle:15°36°
Size: φ122*136
CCT: 3000K /4000K /6000K



MD-PAR38-30WD

Base:E27/E26
Power:30W
AC110v/220V
Beam angle:15°36°
Size: φ122*136
CCT: 2700K /3000K /4000K /6000K



MD-BAR40-30WD

Base:E27/E26
Power:30W
AC110v/220V
Beam angle:100°
Size: φ122*136
CCT: 2700K /3000K /4000K /6000K



MD-AR111-25WAS

AR111
Power:25W
AC220V
Beam angle:15°24° 36°
Size:φ111*50
CCT: 3000K /4000K /6000K



MD-AR111-20WXQ

AR111 with Whip & G53
Power:20W
AC100-277V
Beam angle: 36°45°
Size:φ111*50
CCT: 3000K /4000K /6000K