

MELODY INT'L GROUP LTD



Solar LED Light



 >>> Solar Light



MELODY INT'L GROUP LTD
Tel:+86-750-3329553
sales@melody-lighting.com
www.melody-lighting.com jm-melody.en.alibaba.com
SKYPE: melody-sales
Address:16BLD,Chunhuiyuan,Longlinxilu,Pengjiangqu,Jiangmen,Guangdong,China

"Solar Street Light"

ATL Street Light

Simple, but durable


10+ days continuous lighting even in rainy day
 3 lighting modes to fit what you need
 Material: Aluminium profile
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,500+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 3years



DIALUX road simulation map



Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
STR-ATL20W	20W	6000K	3m	15m	7.55kg
STR-ATL30W	30W	6000K	3m	15m	8.7kg
STR-ATL40W	40W	6000K	4m	15m	10.05kg
STR-ATL50W	50W	6000K	5m	15m	12.55kg
STR-ATL60W	60W	6000K	6m	22m	13.4kg
STR-ATL70W	70W	6000K	7m	28m	15.8kg
STR-ATL80W	80W	6000K	8m	28m	19.4kg
STR-ATL90W	90W	6000K	9m	32m	19.7kg
STR-ATL100W	100W	6000K	10m	32m	20kg



SSL-32-35


SSL-36-310

CLA Street Light



The real thing

10+ days continuous lighting even in rainy day
 Remote controller with 32 lighting modes
 6+ years continuous selling in global market
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,500+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 3years



CE FC RoHS

Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
STR-CLA10W	10W	6000K	2.5m	5m	4.5kg
STR-CLA20W	20W	6000K	3m	9m	7kg
STR-CLA30W	30W	6000K	4m	11m	10kg
STR-CLA50W	50W	6000K	6m	16m	16kg
STR-CLA80W	80W	6000K	8m	21m	18.5kg

DIALUX road simulation map




ARG Street Light



CLASSIC update

10+ days continuous lighting even in rainy day
 Classic- pro with professional LENS and brighter lighting
 Material: Die-casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,500+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 3years



Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
STR-ARG30W	30W	6000K	3m	12m	7.5kg
STR-ARG45W	45W	6000K	5m	15m	10kg
STR-ARG60W	60W	6000K	6m	22m	12.5kg
STR-ARG100W	100W	6000K	8m	24m	13.5kg

DIALUX road simulation map




THE Street Light



5+ years government project's selection

10+ days continuous lighting even in rainy day
 Strongest structural design for weather proof
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,500+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 3years



CE FC RoHS

Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
STR-THE40W	40W	6000K	4m	15m	18kg
STR-THE60W	60W	6000K	6m	18m	25kg
STR-THE80W	80W	6000K	8m	20m	35kg

DIALUX road simulation map



TIT Street Light

Right choice for government project

- 10+ days continuous lighting even in rainy day
- Remote controller with 10 lighting modes
- Bright beyond imagination
- Material: Aluminium profile
- Solar cell: Poly-crystalline
- Battery: Li-ion battery with 1,500+ cycles
- Core technology: ALS2.0/TCS
- Warranty: 3years



Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
STR-TIT20W	20W	6000K	3m	15m	22.9kg
STR-TIT30W	30W	6000K	4m	10m	26.9kg
STR-TIT40W	40W	6000K	5m	20m	31.4kg
STR-TIT50W	50W	6000K	6m	24m	38.7kg
STR-TIT60W	60W	6000K	7m	24m	41.7kg
STR-TIT80W	80W	6000K	8m	30m	49.7kg




 Solar Street Light

TIT Street Light

Detail display

Separated Battery case
for easy maintenance



Angle adjustable
and high brightness
LED panel



Install each lamp 25M between

Shoe Box Light

Brighter & More durable
 7+ days continuous lighting even in rainy day
 Build-in solar panel for keeping original appearance
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,500+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 2years



CE FC RoHS

Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
SHO-BOX15W	15W	5700K	3.5m	11m	8kg
SHO-BOX22W	22W	5700K	5m	15m	10kg
SHO-BOX35W	35W	5700K	6m	18m	12.5kg
SHO-BOX50W	50W	5700K	8m	24m	15kg

HAL Landscape Light

Brighter & More durable
 Operate temperature : -20C° - +65C°
 Build-in solar panel for keeping original appearance
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,500+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 2years



CE FC RoHS


Model type	LED power	Colour temperature	mounting height	installing distance	Luminaire net weight
LAN-HAL20W	20W	4000K	3.5m	14m	4.5kg

 Solar Landscape Light

HON Landscape Light

18th Century Stylish Design

7+ days continuous lighting even in rainy day
2 PIR motion sensor for more sensitive detection
Build-in Solar panel keep appearance more elegant
Material: Die casted Aluminium
Solar cell: Poly-crystalline
Battery: Li-Ion battery with 1,000+ cycles
Core technology: ALS2.0/TCS
Warranty: 2 years





Model type	LED power	Colour temperature	mounting height	Install distance	Luminaire net weight
LAN-HON20W	20W	6000K	3m	14m	6.9kg



You are right! It's solar light with invisible solar panel!

 Solar Landscape Light

HON Landscape Light

18th Century Stylish Design
7+ days continuous lighting even in rainy day
2 PIR motion sensor for more sensitive detection
Build-in Solar panel keep appearance more elegant
Material: Die-casted Aluminium
Solar cell: Poly-crystalline
Battery: Li-ion battery with 1,000+ cycles
Core technology: ALSZ.0/TCS
Warranty: 2 years




 CE FC RoHS

Model type	LED power	Colour temperature	mounting height	Install distance	Luminaire net weight
LAN-HON20WB	20W	6000K	3m	14m	7.2kg

UFO Landscape Light

Simple, the best view




10+ days continuous lighting even in rainy day
 Remote control with 32 lighting modes
 360° lighting
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 2 years



Model type	LED power	Colour temperature	mounting height	Install distance	Luminaire net weight
LAN-UFO20W	20W	6000K	3m	10m	6kg
LAN-UFO30W	30W	6000K	4m	14m	15kg
LAN-UFO50W	50W	6000K	6m	18m	27kg

DIALUX road simulation map





MIR A Bollard Light

Brighter & More durable

Material: Aluminium alloy+PC
Solar cell: Poly-crystalline
Battery: Li-ion battery with 1,000 cycles
Core technology: ALSz.0/TCS
Warranty: 3 years



Model type	LED power	Colour temperature	Luminaire net weight
BOL-MIRO.SWA	0.5W	4000K	1.8kg

 Solar Bollard light

MIR B/C Bollard Light

Brighter & More durable

Material: Aluminium alloy+PC
Solar cell: Poly-crystalline
Battery: Li-ion battery with 1,000 cycles
Core technology: ALS2.0/TCS
Warranty: 2 years



Solar panel



Underground Part



BOL-MIRO.5WB



BOL-MIRO.5WC



Model type	LED power	Colour temperature	Luminaire net weight
BOL-MIRO.5WB	0.5W	4000K	1.9kg
BOL-MIRO.5WC	0.5W	4000K	2.0kg



Gutter Light



Solar gutter Light

GUT-WAL0.6WA
 Solar gutter Light
 Material: Aluminium alloy+PC
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000 cycles
 Core technology: ALS2.0/TCS
 Warranty: 1 year



CE FC RoHS

Model type	LED power	Colour temperature	Luminaire net weight
GUT-WAL0.6WA	0.6W	4000K	0.5kg





Solar gutter Light



GUT-WAL0.6WB

Solar gutter Light

Material: Aluminium alloy+PC
Solar cell: Poly-crystalline
Battery: Li-ion battery with 1,000 cycles
Core technology: ALS2.0/TCS
Warranty: 1 year



Model type	LED power	Colour temperature	Luminaire net weight
GUT-WAL0.6WB	0.6W	6000K	0.5kg





Solar gutter Light



GUT-WAL6WC

Solar gutter Light

Material: Aluminium alloy+PC
Solar cell: Poly-crystalline
Battery: Li-ion battery with 1,000 cycles
Core technology: ALS2.0/TCS
Warranty: 3 years



Model type	LED power	Colour temperature	Luminaire net weight
GUT-WAL6WC	6W	3000K+6000K	1.16kg



 Solar gutter Light



GUT-WAL12WD

Solar gutter Light

Material: Aluminium alloy+PC
Solar cell: Poly-crystalline
Battery: Li-ion battery with 1,000 cycles
Core technology: ALS2.0/TCS
Warranty: 3 years





Model Type	LED power	Colour temperature	Luminaire net weight
GUT-WAL12WD	12W	3000K+6000K	1.5kg



Solar LED Flood Light

*"Solar
flood
light"*

Solar flood light

Warehouse





Amazing in perfect use



Install on the wall

URA Flood Light


Solar flood light 

Amazing in perfect use
 Left Power Indicator
 Indoor & outdoor installation
 Remote control to choose 10%-100% brightness
 Material: Aluminum alloy
 Solar Cell: Poly-crystalline
 Battery : Li-ion battery with 1500 cycles
 Core technology: ALS2.0/TCS
 Warranty: 1 year



Model type	LED power	Colour temperature	mounting height	Install distance	Luminaire net weight
FLD-URA10W	10W	6000K	4m	12m	1kg
FLD-URA15W	15W	6000K	5m	15m	1.1kg
FLD-URA20W	20W	6000K	6m	19m	1.18kg
FLD-URA40W	40W	6000K	10m	26m	2.17kg
FLD-URA50W	50W	6000K	12m	30m	2.7kg





**AMAZING IN TECHNOLOGY,
AGAIN!**

BEE Wall Light

solar wall light



Left Lighting days Indicator
 3 lighting mode with motion sensor
 Constant lighting even in rainy days
 Material: PC
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000+ cycles
 Core technology: ALS2.0/TCS/Sunlight collecting Technology
 Warranty: 1 year



Model type	LED power	Colour temperature	mounting height	Install distance	Luminaire net weight
WAL-BEESW	4W	6000K	4m	10m	0.65kg





"Solar Courtyard Light"

Solar garden Light 

Garden, Courtyard, Road,
Park, Street, Pathway etc.



ESL-15N

PEA Garden Light

Illuminate your secret garden
 7+ days continuous lighting even in rainy day
 Warm White for both lighting & decoration
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 1years



GAR-PEA-1WA



GAR-PEA-1WC



GAR-PEA-4WE



GAR-PEA-1WB



GAR-PEA-4WD

7+ days continuous lighting even in rainy day
 Warm White for both lighting & decoration
 Material: Die casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 1years



Model type	LED power	Colour temperature	PIR	Install distance	Luminaire net weight
GAR-PEA-1WA	1W	3000K	No	5m	1kg
GAR-PEA-1WB	1W	3000K	No	5m	1.5kg
GAR-PEA-1WC	1W	3000K	No	5m	1.75kg
GAR-PEA-4WD	4W	3000K	Yes	5m	2.33kg
GAR-PEA-4WE	4W	3000K	Yes	5m	2.1kg



Underground Light

Solar colorful underground light

Soft lighting by LED panel light, Standard size for easy installation.
 White and blue color changing when people go through
 Size: $\phi 170 \times 55 \text{mm}$
 Material: Die-casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000 cycles
 Core technology: ALS2.0/TCS
 Warranty: 3 years

Place: Park, Garden, Street, Walkway, Bank of swimming pool, etc.



Model type	LED power	Colour temperature	Luminaire net weight
UND-0.3WA	0.3w	6000K	1.16kg



Step Light

Best choice for garden decorative project !

3+ days continuous lighting even in rainy day,
 Best choice for garden decoration
 Material: Die-casted Aluminium
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000 cycles
 Core technology: ALS2.0/TCS
 Warranty: 1 years




Model type	LED power	Colour temperature	Luminaire net weight
STEP-0.5WB	0.5w	3000K	0.5kg

Yard Light



Solar Yard Light 

Illuminate your courtyard



10+ days continuous lighting even in rainy day.
 Sensitive PIR sensor.
 Remote control with 32 lighting modes
 Material: PC
 Solar cell: Poly-crystalline
 Battery: Li-ion battery with 1,000+ cycles
 Core technology: ALS2.0/TCS
 Warranty: 1 year



Model type	LED power	Colour temperature	mounting height	Install distance	Luminaire net weight
YARD-10W	10W	6000K	3m	12m	2.86kg

